

TANK ALARM

3 Channel Float Operated Alarm



This tank alarm has 3 input channels, designed to detect an overflow/high level condition, a low level/re-order condition or mounted in the bund in one, two or three tanks.

- **Multi Purpose:** This tank alarm can be used wherever a high, low or bund level alarm is required in either vertical or horizontal tanks.
- **Alarm Condition:** Float activated switches detect alarm conditions, a maximum of three float switches can be installed, monitoring high, low or bund levels.
- **Suits Most Fuels:** The tank alarm is suitable for many liquids including diesel, gasoil, oils, Adblue®, antifreeze & water. (Not suitable for flammable liquids)
- **Simple to Install:** Easy installation via a wall mounting bracket and fast wiring using our plug and socket field connections.
- **Float Configuration:** Switches installed in the main unit allow easy float configuration.
- **Housing:** Modern, robust and weatherproof to IP55. Supporting the powerful sounder, beacon (mains versions), test and mute buttons and channel indicators.
- **System Test:** Pushing the test button activates a full system test, checking all float switches installed and all other components, the sounder activates as notification of a successful test.
- **Versions:** The tank alarm is available in either 230Vac or 6V battery version. (batteries included). **Optional** 110Vac.
- **Options:** Brass cap - 1½" BSPF cap can be used to install float switch replacing the flat plate fixing supplied. Stainless steel float switch suitable for use with Adblue® and antifreeze.

