

Home > TG product range > Capillary thermostats > TG200

TG200 Control thermostat, pin adjustment


DESCRIPTION

"Compensated" versions available on request

Contact Rating 16(4)A 250Vca, with gold plated contacts 100mV 0,3A.

Gas filled sensing element versions available on request (TG200-Z).

Gold-plated contact versions available on request.



ZOOM

DATASHEET

ADJUSTMENT RANGE/ CALIBRATION (°C)	CONTACTS		BULB		CAPILLARY		CODE
	SPST	SPDT	dimensions (mm)	material	length (mm)	material	
-35 + 35		•	Ø 6,5 x 83	Cu	1500	Cu + PVC	711-F1338-00A
0 + 40		•	Ø 6,5 x 100				711-51338-00A
0 + 90		•	Ø 6,5 x 73				711-11338-00A*
0 + 120		•					711-71338-00A
0 + 210		•	Ø 5 x 80			Cu	711-G1339-00A
0 + 300		•	Ø 3 x 190	Stainless steel	Stainless steel	711-H1337-00A	
Kit - thermostat completed with frame, knob, screws, knob blocking spring - single packed							
0 + 90		•	Ø 6,5 x 73	Cu	1500	Cu + PVC	711-11338-04A*
0 + 120		•					711-71338-03A
Special versions for HOT WATER CLEANERS - with M14x1 connector							
OFF/90		•	Ø 6 x 75	Cu	1500	Cu + PVC	711-X1338-02A
OFF/120		•					711-71338-02A
OFF/150		•					711-X1338-01A
Special version for FRYER MACHINES - with G 1/4 connector							
0/210	gold plated		Ø 5 x 100	Stainless steel	1000	Stainless steel	713-G1227-01A
Special version 62 + 82 - with G 1/4 connector							
62 + 82		•	Ø 6 x 80	Cu	1000	Cu + PVC	711-X7328-03A



ZOOM

* ISPESL approved

Home > [TG product range](#) > [Capillary thermostats](#) > TG200

TG200 Control thermostat, screwdriver adjustment



DESCRIPTION

"Compensated" versions available on request

Contact Rating 16(4)A 250Vca

Gas filled sensing element versions available on request (TG200-Z).

Gold-plated contact versions available on request.



ZOOM

DATASHEET

ADJUSTMENT RANGE/ CALIBRATION (°C)	CONTACTS		BULB		CAPILLARY		CODE
	SPST	SPDT	dimensions (mm)	material	length (mm)	material	
0 ÷ 90		•	Ø 6,5 x 73	Cu	1500	Cu + PVC	712-10338-00A*

* ISPESL approved



ZOOM

Home > TG product range > Capillary thermostats > TG200

TG200 Control thermostat, fixed calibration



DESCRIPTION

"Compensated" versions available on request

Contact Rating 16(4)A 250Vca

Gas filled sensing element versions available on request (TG200-Z).

Gold-plated contact versions available on request.



ZOOM 

DATASHEET

ADJUSTMENT RANGE/ CALIBRATION (°C)	CONTACTS		BULB		CAPILLARY		CODE
	SPST	SPDT	dimensions (mm)	material	length (mm)	material	
90		•	Ø 6.5 x 73	Cu	1500	Cu + PVC	716-90338-00A
100							716-99338-00A