

Home > [TG product range](#) > [Capillary thermostats](#) > TG400

TG400 Limit thermostat, fixed calibration with manual reset



DESCRIPTION

"Compensated" versions available on request

Contact Rating 16(4)A 250Vca, with gold plated contacts 100mV 0,3A.

Gold-plated contact versions available on request.



ZOOM

DATASHEET

ADJUSTMENT RANGE/ CALIBRATION (°C)	CONTACTS		BULB		CAPILLARY		CODE
	SPST	SPDT	dimensions (mm)	material	length (mm)	material	
100		•	Ø 6,5 x 73	Cu	1500	Cu + PVC	971-99338-00A*
100	gold plated						973-99238-00A
Special version for FRYER MACHINES - with G 1/4 connector							
235	gold plated		Ø 5 x 100	Stainless steel	1000	Stainless steel	973-2X227-02A**

* ISPEL approved

** Failure Safe function not available.



ZOOM

[Home](#) > [TG product range](#) > [Capillary thermostats](#) > TG400

TG400 Limit thermostat, screwdriver adjustment and manual reset



DESCRIPTION

"Compensated" versions available on request

Contact Rating 16(4)A 250Vca, with gold plated contacts 100mV 0,3A.

Gold-plated contact versions available on request.



DATASHEET

ADJUSTMENT RANGE/ CALIBRATION (°C)	CONTACTS		BULB		CAPILLARY		CODE
	SPST	SPDT	dimensions (mm)	material	length (mm)	material	
90 + 110		•	Ø 6,5 x 73	Cu	1500	Cu + PVC	961-11338-00A
90 + 110		gold plated					963-11338-00A
70 + 90		•					961-90338-00A
70 + 90		gold plated					963-90338-00A
Flue gas safety limiter version - with washer and plate for bulb fixing							
70 + 110		gold plated	Ø 5 x 90	Cu	1500	Cu + PVC	963-11338-20B



[Home](#) > [TG product range](#) > [Capillary thermostats](#) > TG400

TG400 Limit thermostat, automatic reset

DESCRIPTION

"Compensated" versions available on request

Contact Rating 16(4)A 250Vca, with gold plated contacts 100mV 0,3A.

Gold-plated contact versions available on request.



DATASHEET

ADJUSTMENT RANGE/ CALIBRATION (°C)	TYPE OF ADJUSTMENT/ CALIBRATION		CONTACTS		BULB		CAPILLARY		CODE
	screwdriver	fixed	SPST	SPDT	dimensions (mm)	material	length (mm)	material	
100		•	gold plated		Ø 6,5 x 73	Cu	1500	Cu + PVC	974-99238-00A
90 + 110	•		•						962-11238-00A
90 ÷ 110	•		gold plated						964-11238-00A