

OIL UP FEEDER

OUF-88 & OUF-88 Maxi

OUF-88



PUMP TYPE	Suction Solenoid Pump
LIFTING HEIGHT (MAX.)	8 m. vertical (8 mm I.D. tube)
MÁX. HORIZONTAL DISTANCE	100 m. horizontal (8 mm I.D. tube)
OUTLET FLOW RATING (8 mm I.D. tube)	8 l/hr at: 8 m vertical & 25 m horizontal 15 l/hr at: 5 m vertical & 25 m horizontal
INLET CONNECTION	3/8" F BSP
OUTLET CONNECTION	3/8" F BSP
OVERFLOW OUTLET CONNECTION	1/2" F BSP
POWER SUPPLY	AC 230V, 50Hz
POWER CONSUMPTION	50 W
RESERVOIR TOTAL CAPACITY	3,5 Litre (Maxi: 12 litres)
DIMENSIONS (W x D x H)	240 x 130 x 335 mm (Maxi: 350 x 225 x 345)
WEIGHT	3 kg (Maxi: 4 kg)
FUEL TYPE	Kerosene & Diesel Oil



Models

- OUF-88 Oil Lifter Only
- OUF-88 Maxi Oil Lifter Only
- OUF-88 Oil Lifter c/w Leak Detection Kit + Tray
- OUF-88 Maxi Oil Lifter c/w Leak Detection Kit + Tray

Product code

6808000-A
6808010-A
6808020-A
6808030-A

Optional Fittings

- Leak Detection Kit & 245 mm Tray for OUF-88
- Leak Detection Kit & 350 mm Tray for OUF-88 Maxi

Product code

6800232-A
6800233-A

